


MCN System Performance Toolkit

etc.), its power is the ability to give a notification about possible system problems before they escalate into larger ones.

Some features of the System Watchdog module include:

- User-programmable Look-Back Time for activity,
- User-defined channels & receivers to watch,
- Alerts logged on screen, disk, & printer.



Channel	Receiver	Description	Hardware Info	Watchdog	Expired
PD	911 Center		HIB-IP 1:000:0:1	No Vote	Tue, Sep 8, 15:43:47
PD	911 Center		HIB-IP 1:000:0:1	No Receive	Tue, Sep 8, 15:43:47
PD	West High		HIB-IP 1:000:0:2	No Vote	Tue, Sep 8, 15:43:47
PD	West High		HIB-IP 1:000:0:2	No Receive	Tue, Sep 8, 15:43:47
PD	Water Tank		HIB-IP 1:000:0:3	No Vote	Tue, Sep 8, 15:43:47
PD	Water Tank		HIB-IP 1:000:0:3	No Receive	Tue, Sep 8, 15:43:47
PD	University Cntr		HIB-IP 1:000:0:4	No Vote	Tue, Sep 8, 15:43:47
PD	University Cntr		HIB-IP 1:000:0:4	No Receive	Tue, Sep 8, 15:43:47
PD	General Hospital		HIB-IP 1:000:0:5	No Vote	Tue, Sep 8, 15:43:47
PD	General Hospital		HIB-IP 1:000:0:5	No Receive	Tue, Sep 8, 15:43:47
PD	Greenhills		HIB-IP 1:000:0:6	No Vote	Tue, Sep 8, 15:43:47
PD	Greenhills		HIB-IP 1:000:0:6	No Receive	Tue, Sep 8, 15:43:47
PD	West Chester		HIB-IP 1:000:0:7	No Vote	Tue, Sep 8, 15:43:47
PD	West Chester		HIB-IP 1:000:0:7	No Receive	Tue, Sep 8, 15:43:47
PD	Airport		HIB-IP 1:000:0:8	No Vote	Tue, Sep 8, 15:43:47
PD	Airport		HIB-IP 1:000:0:8	No Receive	Tue, Sep 8, 15:43:47
Admin	911 Center		HIB-IP 1:000:0:1	No Vote	Tue, Sep 8, 15:43:47

Alarm Window

Data Miner

The **Data Miner** module is a display and export program that allows the user to view the Activity Summary Files generated by the System Watchdog service. System activity data can be viewed for each of the MCN channel being monitored. Activity times and counts can be viewed for each of the following events:

- Vote,
- Receive,
- Disable,
- Fail.


Using this information, the Data Miner viewer module can be used to help diagnose system problems. Data Miner makes it easy to see at a glance the activity level on receivers and channels, and can be used to indicate:

- Channel loading statistics,
- Receiver performance,
- Needed radio maintenance.

It can also be used for site-selection planning and administrative reports.

Exporting Data to Excel

The DataMiner program uses Export Definitions to transfer data to Microsoft Excel. A typical Export Definition is shown in the screen below. The exported data includes receiver names and descriptions, along with the selected activity type (Vote Time, Vote Count, Receive Time, Receive Count, etc.).



Channel	Watch Dog	Export Time	Export Count
CH TAC 1	Disabled	Yes	Yes
	Vote	Yes	Yes
	Rx	Yes	Yes
	Fail	Yes	Yes
CH 2 AREA A	Disabled	Yes	Yes
	Vote	Yes	Yes
	Rx	Yes	Yes
	Fail	Yes	Yes
CH 3 AREA B	Disabled	No	No
	Vote	Yes	Yes
	Rx	Yes	Yes
	Fail	Yes	Yes
CH 4 AREA E	Disabled	No	Yes
	Vote	Yes	Yes
	Rx	Yes	Yes
	Fail	Yes	Yes
CH 5 AREA D	Disabled	No	No
	Vote	No	No
	Rx	No	No
	Fail	No	No
CH 6 AREA C	Disabled	Yes	Yes
	Vote	Yes	Yes
	Rx	Yes	Yes
	Fail	Yes	Yes
CH 7 CAR TO CAR	Disabled	Yes	Yes

Separate files are generated for each radio channel. Activity times and counts can be summarized by hour or by day.



External Analysis with Excel

Possible uses of Microsoft Excel include:

- Total Channel Vote Time,
- Percentage of Vote Time per Channel by Receiver,
- Average Vote Length by Receiver,
- Graphs of Receiver or Channel Activity,
- Percentage of Vote Time vs. Receive Time by Receiver.

Two examples are shown below.

Typical Graphs from Excel



Ordering Information for System Performance Toolkit

Product	CTI Order Number	Maximum Receivers or I/O Points Monitored	Licensed Installations
SPT Level 1	S1-61434	128	1
SPT Level 2	S1-61435	512	1
SPT Level 3	S1-61436	Unlimited (Limited only by MCN Server Capability)	1

Receiver and Point Quantities

Receivers and I/O point quantities are calculated based on the maximum number of receivers or I/O points in the MCN module or IP comparator configured in the customer's system.

Examples:	CIB Module	8 Receivers or 32 I/O Points
	AIB Module:	8 to 64 Receivers (Banks of 8)
	MLC 8000	64 Receivers
	GCM 8000	64 Receivers
	GRV 8000	96 Receivers
	GPIO-1208C	20 Points

For example, SPT Level 1 software would support up to (2) MLC 8000 or GCM 8000 comparators.

Specifications

Application Type	Native 32 Bit Windows Application
Operating System	Win 10 Pro 64 Bit or newer
PC Requirements (min.)	Intel I3 – 3.0 GHz quad-core processor or better. At least 8 GB RAM
Requires	MCN Comparator Display System MCN Advanced Server Software MCN Server 8000 Software Microsoft Excel 2010 or up for exports
Runs on	Separate PC connected over LAN.
Alerts Based on	No Vote or No Receive activity (selectable)
Activity Look-Back Time	Global, 1 to 100 Hours, user configured
Receiver Configuration	- Receiver configuration retrieved from MCNRCD Server database - Receiver Watch / Ignore state specified by user
Alert Audio Outputs	Selectable .WAV File
Logging	Errors logged to Screen, Printer, Disk
Activity Summary File	1000 hours Time (seconds) and Counts for: -Vote -Receive - Disable - Fail
Export File Format	XLS 1 file per Radio Channel Microsoft Excel required.

Feature Comparison

Feature	MCN RCD Server	System Performance Toolkit
Alerts:		
Vote	✓	
Receive	✓	
Disable	✓	
Fail	✓	
Transmit Select	✓	
Receiver Timed Inactivity		✓
Vote Timed Inactivity		✓
Programmable Look-Back Time		✓
RCD Server Not Running		✓
Logging:		
Screen	✓	✓
Disk	✓	✓
Printer	✓	✓
Audible	✓	✓
Email	✓ (Not for MCN Server 8000)	
Data Export (Requires Microsoft Excel):		
Export Data		✓
Scheduled Exports		✓